



Uszy nośne SR-UNC (gwint calowy UNC)



- Forged steel - Quenched & Tempered.
- Working Load Limits shown are for in-line pull. For angle loading, see Warnings & Applications.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- Recommended for in-line pull.
- threaded UNC.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these bolts meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.

Size (in)	Working Load Limit (kg)	Weight Each (kg)	Dimensions (mm)						
			B	C	D	E	F	G	H
3/8	200	.03	13.0	28.7	19.1	47.0	4.9	13.5	19.6
1/2	400	.05	13.0	35.1	22.4	54.6	6.4	15.0	24.1
5/8	640	.07	17.0	41.1	25.4	64.3	7.9	17.5	26.5
3/4	1000	.11	20.5	49.5	30.2	77.7	9.7	23.1	32.8
7/8	1800	.25	27.0	60.5	35.1	96.0	12.7	28.7	38.9
1	2500	.42	30.0	70.0	38.1	108	16.0	35.1	43.4
1-1/8	4000	1.05	38.0	95.5	51.0	142	22.4	46.0	58.4
1-1/4	5000	1.42	69.8	107	57.1	183	24.6	52.3	59.7
1-1/2	6000	1.77	45.0	114	63.5	171	25.4	58.0	69.3
1-3/4	8500	3.12	54.0	140	76.0	207	31.8	70.0	83.3
2	14000	4.58	95.2	159	88.9	266	35.0	76.2	91.4
2-1/2	17300	8.71	102	194	101	313	46.0	85.9	114

5:1 Design Factor. Maximum Proof Load is 2 times the Working Load Limit. *All bolts threaded UNC.

